



SPECIFICATIONS, M1330

DIMENSIONS

	IMPERIAL	METRIC
Overall height	50.5 in	128 cm
Overall length	70 in	179 cm
Overall width	36 in (6" Tracks) 39 in (9" Tracks)	91 cm (6" Tracks) 99 cm (9" Tracks)
Weight	2100 lbs	953 kg
Lift Height to pin, max	72 in	183 cm
Wheel base/track length	35 in	89 cm
Track width, max	9 in	23 cm
Ground clearance	6.5 in	17 cm
Platform height	11 in	28 cm
Carrying Capacity	2700 lbs	1227 kg
Tipping capacity	1330 lbs	603 kg
Traction (Push-Pull) Power	1100 lb	499 kg
Rear attack angle	15°	
Dump angle	85°	

OPERATION

	IMPERIAL	METRIC
Ground drive speed		
Forward	3.5 MPH	5.5 KPH
Reverse	3.5 MPH	5.5 KPH
Ground pressure	5 PSI (6" Tracks) 3.33 PSI (9" Tracks)	34.5 KPA (6" Tracks) 23 KPA (9" Tracks)

HYDRAULIC SYSTEM

	IMPERIAL	METRIC
Hydraulic oil flow	14 GPM	53 LPM
Pressure	2900 PSI	20 MPA

FLUID CAPACITIES

	IMPERIAL	METRIC
Fuel tank	10 gal	37 L
Hydraulic reservoir	18 gal	69 L

POWER

	Kubota D1105T	Kohler
Engine:	Diesel	Gas
Fuel:	Liquid	Liquid
Cooling medium:	3	2
Number of cylinders	3.07 in (78.0 mm)	3.3 in (83 mm)
Bore	3.09 in (78.4 mm)	2.7 in (69 mm)
Stroke	3000 RPM	3600 RPM
Rated speed:	33 HP (24.5 KW)	30 HP (22.4 KW)
Estimated Net power		