RAMROD

ESTATE SERIES



500 4WD 575 TRACK Mini Skid Loaders - Ideal for Estate Home Owners and Light Utility and Construction Applications



RAMROD Means Performance - Bette

Co Places only RAMI

Two Great Economical Estate Models To Serve You..



MODEL 500 Four Wheel Drive



MODEL 575
Track Drive

Two models of RAMROD "Hydraulic Self-Propelled" Mini Loaders deliver big performance in small places. Machines are driver-friendly, with an unobstructed view of all working conditions, with quick-learningtime, and equipped with Self-Centering Controls which "Stop Dead" all drive, lift, or levelling movements when the operator's hands are removed from the controls. Machines are easily transported in a trailer or pick-up truck.

Choose The Model That Best Suits Your Requirements

RAMROD - 4WD - Electric Start - 4" Tires (30"Wide) RAMROD - 4WD - Electric Start - 8" Tires (38"Wide)

RAMROD - Electric Start - 6" Tracks (34" Wide) RAMROD - Electric Start - 9" Tracks (40" Wide)

- Choice of Tire & Track Widths
- Safety Louvered Front Panel Engine Shield
- Tropical Air Flow Cooling
- Lift & Tie Down Lugs
- Enclosed Drive Chain
- Powder Paint Finish
- Dripless Hydraulic Couplers
- Multi Hour Fuel Capacity



Give Yourself the Competitive Edge - Choose RAMROD

er Features - Economy - More Value

ROD Mini Loaders Can!

Quick-On-Quick-Off Attachments

Change any of the versatile attachments in seconds reducing downtime and increasing productivity with the right tool.

Safe-Load Self-Levelling Loader

Prevents load "fall back" on operator at full height & eliminates the danger of losing a load during the raising and lowering process.

Superior Bucket Rollback and Dump Angle

20° Rollback Angle lets you easily fill and carry material in bucket. The 80° Dump Angle empties the load completely each time & prevents sticking to bucket.

Easy to Operate Single Hand Palm Steering

RAMROD Exclusive & Unique Single Handed Steering Control System makes this machine very user friendly.



More Features and Benefits to Enhance your Investment



Low Step Non-Slip Stand-On Platform

Safe & easy on /off slip resistant platform with side & rear protection.

Great Lift Height and Lift Capacity

4WD Model 500 Lifts 500 lbs (227 kg) and Track Model 575 lifts 575 lbs (262 kg). Loader lift height to hinge pin is 66" (1690 cm).

Narrow Width Models

Compact 30" Overall width of 4WD model gets machine into confined areas, elevators, doorways, and manoeuvers easily in obstructed areas.

Parts and Service Support - Warranty

Same day processing of parts & service requests from worldwide network of dealers and by factory. 3 year structural warranty of machine frame & arms & 1 year on other manufacturers components.

Auxilliary Hydraulic Outlets (Optional)

Conveniently loaded for easy access on front of lift arms to power various attachments available.

Start Your Own Business With RAMROD Mini Loader and Easy to Use

Quick-on, Quick-off Attachments



Material Bucket - 31"-36"-42"



Post Hole Augers



Backhoes - Digs 6'6" with a 9" Reach



Brooms - 24" Dia x 36"Wide Angles -Steel & Poly Bristles



Carry All Leveler -48" Wide x 24" Deep



42" Dozer Blade



Grapple Bucket



Hay & Manure Fork - 39" Wide with 1 1/4" x 24" Tines



Hydraulic Hammer - 500 to 1300 Blows/ minute at up to 184ft/ lbs (86gpm)



Loose Material Handler - 35" Wide -Opens 68" Hydraulically



Mini Dipper - 60" Dig, 12" Bucket, 86" Dump Height and 70" Bucket Clearance



Multi-Purpose Toolbar Ripper - Tow bar, Boom



Pallet Lift Fork - Back Guard with 2 - 41" Tines Max 30" Wide



Ripper - with 2 - 12" Long Teeth



Snow Blower - 35" Wide - 2 Stage -Hydraulic Drive -Adjustable Spout



Tiller - 36" Wide - 6" Deep Forward and Reverse Tine Rotation



Trencher - 24" Cutting Depth 4" to 6" Chain Widths



Tooth Bar - For 31", 36" & 42" Buckets

Also 3 in 1 Tool Bar - Slasher/Brush Cutter/ Flail Mower - Call RAMROD for other attachments available

Specification and Features

Gasoline Engine Horsepower Traction (Push-Pull) Power lbs(Kg) Lift Capacity lbs (kg) **Carrying Capacity** lbs (kg) Lift Height to Pivot Pin inches (mm) Hydraulic Pressure PSI (Bar) Hydraulic Flow/Aux Outlets GPM (L/Min) Narrowest Width inches (mm) Widest Width inches (mm) **Body Height** inches (mm) Length with Bucket inches (mm) Length less Bucket inches (mm) **Ground Clearance** inches (mm) Rollback Fully Raised Rollback at Ground Dump Fully Raised Dump at Ground Level

Model 500 4WD

Model 575 1
13.5HP
995 (452)
575 (262)
975 (443)
66 (1690)
2100 (144)
6.3 (2.4)
34 (864)
40.0 (1016)
48.5 (1232)
77.5 (1968)
58.5 (1486)
4.75 (122)
20º
20º
$80_{\bar{o}}$

809

1380 (627)

Model 575 Track



Specifications Subject to Change Without Notice

Stay Ahead With Ramrod - Stay Ahead With The Best

80⁰

lbs (kg)

1150 (500)



Weight



www.ramrodequip.com

