



SPECIFICATIONS, M1350

DIMENSIONS

	IMPERIAL	METRIC
Overall height	51.5 in	131 cm
Overall length	67 in	170 cm
Overall width	42 in	131 cm
Weight	2575 lbs	1168 kg
Lift Height to pin, max	72 in	183 cm
Wheel base/track length	31 in	79 cm
Track width, max	9 in	23 cm
Ground clearance	6.5 in	17 cm
Platform height	11 in	28 cm
Carrying Capacity	2700 lbs	1227 kg
Tipping capacity	1350 lbs	614 kg
Traction (Push Pull) Power	1700 lbs	771 kg
Rear attack angle	26°	
Dump angle	85°	

OPERATION

	IMPERIAL	METRIC
Ground Drive Speed		
Forward	3.5 MPH	5.5 KPM
Reverse	3.5 MPH	5.5 KPM
Ground pressure		

HYDRAULIC SYSTEM

	IMPERIAL	METRIC
Hydraulic oil flow	14 GPM	53 LPM
Pressure	3000 PSI	20,684 KPA

FLUID CAPACITIES

	IMPERIAL	METRIC
Fuel tank	8 gal	30 L
Hydraulic reservoir	10 gal	37 L

POWER

	Kubota/Daedong	Kohler
Engine:	Diesel	Gas
Fuel:	Diesel	Gas
Cooling medium: Liquid	Liquid	Liquid
Number of cylinders	3	2
Bore	3.07 in (78.0 mm)	3.3 in (83 mm)
Stroke	3.09 in (78.4 mm)	2.7 in (69 mm)
Rated speed:	3000 RPM	3600 RPM
Estimated Net power	33 HP (24.5 KW)	30 HP (22.4 KW)